

Wireless Analog Molded Case Battery Clocks

GENERAL INFORMATION

- Clock hour & minute hands: Black
- Clock second hand:.....Red
- Battery life:..... Up to 5 years
- · Rear panel indicator: Red LED indicates receiver wake-up and time sync
- Receiver sensitivity: 10uV per meter
- Antenna type: External
- Time to synchronize: Initial sync time is 5-10 minutes
- Time accuracy: ±1 second to SiteSync IQ® Master Clock

PHYSICAL / ENVIRONMENTAL SPECIFICATIONS

- Operating temperature: 41°F to 131°F

Note: These clocks are intended for use with a SiteSync IQ Wireless Clock System.





ORDERING INFORMATION

Part #	Description
SQ46BADD304BP	10" Round, surface mount
SQ45BADD?04BP	10" Round, flush mount
SQ56BADD304BP	12" Round, surface mount
SQ55BADD?04BP	12" Round, flush mount
SQ93BADD204BP	12" Round, double dial wall mount
SQ92BADD204BP	12" Round, double dial ceiling mount
SQ66BADD304BP	15" Round, surface mount
SQ65BADD?04BP	15" Round, flush mount
SQ63BADD204BP	15" Round, double dial wall mount
SQ62BADD204BP	15" Round, double dial ceiling mount


Add L to the end of the Part # for personalized dial option


Note: If flush mounting in an existing backbox, change the ? in the Part # to specify correct hanger type from the list below: 1=National Time 5=Simplex[®], Dukane, Lathem 6=Cincinnati, Edwards, Faraday, Honeywell 8=Standard[™] Electric

Note: Other dial styles and case colors available

Note: These clocks are intended for use with a SiteSync IQ® Wireless Clock System.

OUTSIDE DIMENSIONS			
SIZE	Α	В	С
Surface			
10"	103⁄8"	2 ¹ / ₂ "	N/A
12"	13¼"	2 ¹ / ₂ "	N/A
15"	16"	2 ¹ / ₂ "	N/A
Flush			
10"	103⁄8"	2"	N/A
12"	13¼"	2"	N/A
15"	16"	2"	N/A
Double Dial			
12"	13¼"	15"	85/8"
15"	16"	19 ¹ / ₄ "	85⁄8"








A

Surface mount plastic



Plastic double dial profile



At American Time, we continually strive to improve our products to meet our customers' needs and to provide the best possible value. The above specifications are believed to be correct, are subject to change without notice and may otherwise vary from the above. Please call if you need verification of any specifications or the suitability of a particular product for a particular application.